

Your vessel is on **FIRE!** You only have seconds....
"PULL THE PIN AND THROW IT IN"



Wall mount steel bracket*

AEROSOL FIRE SUPPRESSION TOOL
NON-TOXIC • UP TO 5,300CU.FT.OF COVERAGE • 15YR. SHELF LIFE

Waterproof storage case (MILSPEC)*

**REMOVES UP TO 1,000°F
 IN 60 SECONDS OR LESS!**

Innovation in Fire Suppression Since 2012 • www.flameguardusa.com • tollfree 855-377-2100 email sales@flameguardusa.com
 X-Tinguish® is a trademark of Flame Guard USA, LLC Copyright ©2021 Flame Guard USA, LLC All Rights Reserved
 *Special order



15 YEAR SHELF-LIFE • 5-YEAR BATTERY

NON-TOXIC-NON-CORROSIVE-NON-CONDUCTIVE

NO OZONE DEPLETION POTENTIAL (ODP) • NO GLOBAL WARMING POTENTIAL (GWP)

WORKS TO -65°F (-54°C) • NON-PRESSURIZED • DOES NOT REDUCE OXYGEN (O²)



DESCRIPTION

The X-Tinguish® X-Treme is used by Firefighters, and First Responders in all industries as a highly effective suppression tool against early stage and fully developed fires. When Seconds Count, deploy the X-Tinguish® X-Treme directly into the fire. Simple to operate. Saves lives and Property.

OTHER FEATURES

- Extraordinary knock down & suppression
- Can eliminate flashover and backdraft
- NOT pressurized!
- 5-year battery life
- LED light turns red when the unit is activated

SPECIFICATIONS

Total weight	13.90lbs. / 6.3 kg.
Compound weight	6.40 Lbs. / 2.9 kg.
Volume coverage	≤ 5,300cu.ft. / 150 m ³
Discharge time	33-35 seconds
Activation method	Manual pull pin
Operational to	-65°F / -55°C

1000 Butterfield Road • Suite 1029
 Vernon Hills, IL USA 60061
 Url: <https://www.flameguardusa.com>

Email: sales@flameguardusa.com

Tollfree: (855) 377-2100 Direct: (815) 219-4074

